



Proudly Australian Built



Product Information

SMITHWELD ENTERPRISES PTY LTD

Features

- * Boom reach, 3M
- * Boom height, nozzle to floor
2.5m (standard)
3.5m with extension.
- * Variable speed range (vertical)
0 – 300mm/min.
- * Variable speed range in/out
0 – 500mm/min.
- * Quality hand pendant with
shielded cable supplied
as standard.
- * All Welded Construction.
- * 200mm cross seam adjustment.
- * Boom base, 1900x1300 with
geared swivel base on 6 x groove
wheels.
- * Safety limit switch on all 4 points.
- * All cables secured through boom.
- * Laser alignment light standard.
- * Fully enclosed electrical cabinet.

OPTIONAL FLUX RECOVERY
SYSTEM AVAILABLE AT THE
WELDING HEAD.

**Smithweld Enterprises
Pty Ltd**

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670
Fax: 61 8 9470 6680

Email: sales@smithweld.com

SAW welding boom Model SW-3x3B



Specifications

- | | |
|-----------------|------------------------|
| * Capacity: | 3 x 3 metre |
| * Voltage: | 220-240V single phase. |
| * Speed control | via "Delta" controls |
| * Protection | Overload & current. |

External Dimensions

- | | |
|-------------|------------------------------------|
| Length: | 4.0m. |
| Width: | 1.3m. |
| Height: | 3.2M (standard).
4.2M (special) |
| Net Weight: | 1400kg |

