



**Proudly Australian Built**



## Features

- \* Turning Capacity at Face Plate 3000kg.
- \* Tilt Capacity at Face Plate 3000kg max.
- \* Variable Speed Range 0 – 2 rpm. on Rotation.
- \* Quality digital controllers with safety shut-down and overload protection.
- \* 2 x Motorised Axis.
- \* Height Adjustment of Plate Centre 600 – 900mm for 3<sup>rd</sup> Axis. (Manual)
- \* Quality hand pendant with 5m of Shielded Cable.
- \* Arc on Interface standard on Hand Pendant.
- \* Built-In Rotary 500Amp. Welding Earth.
- \* Face plate diameter 600 or 800 must be stipulated on your order.

## Safety

All gear drives are fully covered to prevent accidental catching of cloths or fingers.

## Test data

800kg load @1200mm from plate  
2000kg load @ 500mm from plate

**Smithweld Enterprises  
Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670  
Fax: 61 8 9470 6680

Email: sales@smithweld.com

# *Product Information*

SMITHWELD ENTERPRISES PTY LTD

## *PIPE POSITIONER*

### *3000kg Capacity*

### *Model SW-3TP-3-3*



## Specifications

Capacity on rotation: 3000kg.  
Voltage: 220-240V.  
Programmable digital control  
Industrial pendant: on/off, tilt and speed control.

## External Dimensions

Length: 1500mm.  
Width: 850mm.  
Height: 1250mm when plate is vertical.  
Net Weight: 650kg.

Shipping Box: 1500L x 800W x 1000H

