



Proudly Australian Built



Product Information

SMITHWELD ENTERPRISES PTY LTD

PIPE ROTATOR 4000kg Capacity

Model SW-4TR-4-100-1200



Optional extra
Foot control
Model SW-10 F
With 10 metres
of rubber cable.

Features

- * Turning capacity 4000kg (max), when used with min of one idler.
- * Pipe diameter range 100 – 1200mm.
- * Wheel centres 280,430 & 560mm
- * Variable speed range .01 – 3rpm.
- * Quality hand pendant supplied as standard
- * All Welded Construction.
- * Solid 250mm. rubber wheels.
- * Precision aligned frame for No creep on rotation.
- * Recessed controls.
- * Optional foot switch SW-10F.
- * Idler Pt No SW-1.5TRI-2 is required with main drive unit when turning 4000kg max load. Idler unit. (Idler weight 61kg)
- ** Additional Idlers Recommended For Pipe Over 4 metres Long.

Specifications

Capacity:	4000kg.
Voltage:	220-240V single phase.
Speed range:	0 – 3rpm.
Overload protection:	current limiting Digital control.

External Dimensions

Depth:	950mm.
Width:	800mm.
Height:	340mm.
Net Weight:	138kg
Shipping Box (mm)	950D x 800W x 440H
Last updated 26/01/09	(on pallet)

**Smithweld Enterprises
Pty Ltd**

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670
Fax: 61 8 9470 6680

Email: sales@smithweld.com

