



Proudly Australian Built



Technical Features

- * Turning capacity at face plate 2000 Kg central load
- * Tilt capacity at face plate 2000 Kg max
- * Variable speed range 0 – 2 rpm on rotation
- * Quality digital controllers with over (V) (A) & (Nm) protection
- * Recessed digital speed readout
- * Height adjustment of plate centre 600 – 900mm for 3rd Axis (Manual)
- * Quality hand pendant with 5m of shielded cable
- * Hold down 4 jaw chuck (optional extra) SW-800C
- * Built-In rotary 500 A. welding earth with bearing support
- * Face plate diameter 800 mm
- * OHS - Rotation gear is fully covered to prevent dust ingress & any harm to the operator.

Test data for tilt
800 Kg load @1200mm from plate
2000kg max load @ face plate

- * Electrical compliance to AS/NZS 3000-2009

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

PIPE POSITIONER **2000kg Capacity** **Model SW-2TP-2**



Optional extra

Foot control
Model SW-10F
With 10 metres of rubber cable



Specifications

Rotation Capacity:	2000 Kg
Voltage:	220-240 VAC 1PH
Industrial pendant:	tilt, rotate speed control & E-stop

External Dimensions

Length:	150 cm
Width:	85 cm
Height:	125 cm
Net Weight:	650 Kg
Shipping size:	150cmL x 80cmW x 100cmH

© 2015

