



**Proudly Australian Built**



## Technical Features

- \* Turning capacity 3000 Kg
- \* Pipe diameter range 100 – 1200 mm
- \* Wheel centres 280,430 & 560mm
- \* Variable speed range 0 – 3 rpm
- \* Recessed controls & digital speed readout for precise control of welding speed
- \* Quality hand pendant, with 10m of EM shielded cable, supplied as standard (SW-XTR-LT10)
- \* Precision aligned all welded frame for no creep on rotation
- \* Solid 250mm. rubber wheels
- \* Optional Heavy-duty foot control (SW-10F)
- \* Additional idler (45 Kg) SWL 1500 Kg (SW-1.5TRI-2) recommended for pipe sections over 4 metres long.
- \* Electrical compliance to AS/NZS 3000/2009

**Smithweld Enterprises Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

# Product Information

SMITHWELD ENTERPRISES PTY LTD

## PIPE ROTATOR SWL 3000 Kg Capacity Model SW-3TR-2



**Optional**  
Extra Idlers (45 Kg)  
(SW-1.5TRI-2)  
SWL 1500Kg



**Optional**  
Twin axis rotary  
welding earth  
SW-XYREC-300/  
400

### Specifications

*Capacity:	3000 Kg
*Voltage:	220-240 VAC
*Speed range:	0 – 3rpm
*Overload protection:	Current (A) Voltage (V) Torque (Nm)

### External Dimensions

Length:	850 mm
Width:	270 mm
Height:	360 mm

Net Weight:	98 Kg
Shipping Box (mm):	850L x 270W x 460H



**Optional**  
H-duty Foot control  
SW-10F with 10m  
of rubber cable



© 2015