



**Proudly Australian Built**



## Technical Features

- \* Fully sealed unit, protecting Motor/gearbox and electrical system
- \* Load capacity 4000 Kg, when combined with a minimum of one SW-1.5TRI-2 idler
- \* Pipe diameter range 100 – 1200mm
- \* Wheel centres 280,430 & 560mm
- \* Variable speed range .01 – 3rpm
- \* Recessed digital speed readout for precise control of welding speed.
- \* Quality hand pendant supplied as standard SW-XTR-LT10
- \* Solid 250mm rubber wheels
- \* Precision aligned all welded frame for no creep rotation
- \* Idler unit SW-1.5TRI-2 is required with main drive unit when turning 4000 Kg max load (Idler weight 45 Kg)
- \* Additional Idlers recommended for pipe over 4m long, depending on weight/m
- \* Electrical compliance to AS/NZS 3000/2009

# Product Information

SMITHWELD ENTERPRISES PTY LTD

## PIPE ROTATOR 4000kg Capacity Model SW-4TR-4



**Optional**  
Twin axis rotary  
welding earth  
SW-XYREC-300/400



**Optional**  
Mobile pipe stand  
Please go to web page  
for further information

**Optional**  
H-duty foot control  
with 10m of rubber  
cable SW-10F

## External Dimensions

Depth:	950 mm
Width:	800 mm
Height:	340 mm
Weight:	134 Kg
Shipping Box (mm)	950D x 800W x 440H

**Smithweld Enterprises  
Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670  
Email: sales@smithweld.com



© 2016