



Proudly Australian Built



Technical features

- * Turning capacity 6000 Kg, Idler qty will depend on wall thickness/diameter of pipe.
- * Pipe/vessel diameter range 300 – 2000 mm
- * Variable wheel centres
- * Variable speed range .01 – 2rpm
- * Quality hand pendant **SW-XTR-HT10** with 10m shielded cable, mil spec plug as standard. Operations, fwd /rev, variable speed & E-stop
- * Recessed controls & digital speed readout for precise control of welding speed.
- * 400 mm DIA x 150 mm wide solid rubber wheels
- * Precision aligned all welded frame for no creep rotation
- * Main drive unit SWL 6000 Kg, when used with at least one Idler **SW-3TRI-2**
- * Electrical compliance to AS/NZS 3000-2009

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

PIPE ROTATOR 6000kg Capacity

Model SW-6TR-2



Optional
Twin axis rotary
welding earth
SW-XYREC-300/400



Optional
H-duty foot control
SW-10F with 10m
of rubber cable

Specifications

Capacity max	6000 Kg
Voltage:	220-240 VAC 1 ph
Speed range:	0 – 3 rpm
Overload protection:	Current (A) Voltage (V) Torque (Nm)

External Dimensions

Length:	180 cm
Width:	55 cm
Height:	34 cm
Weight:	258 Kg main drive 145 Kg idler



© 2014