



Proudly Australian Built



Technical Features

- * Turning capacity at face plate 1000 Kg (balanced load).
- * Top roll capacity 1000 Kg.
- * Digital speed read out, inbuilt to the main body
- * Variable speed range 0 – 4 r.p.m.
- * All welded construction.
- * Sealed unit to protect motor/gearbox and controls.
- * Solid 200mm. rubber wheels.
- * Built-in rotary 500 A welding earth.
- * Recessed controls.
- * Adjustable top rolls for pipe diameters. 50 – 300mm.
- * 12mm lifting eyes and fork lifting slots.
- * Electrical compliance to AS/NZS 3000-2009.

Optional extra, 300mm lathe chuck as displayed.

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670
Fax: 61 8 9470 6680

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

PIPE POSITIONER/ROTATOR

1000kg Capacity Model SW-700P-AC



Mechanical hand crank 0-90°, on left side of unit with safety stop

Optional extra
Elite Gun-Torch Support & Alignment System

Optional extra
Hand Remote Control Model SW-XTR-LT10 With 10 metres of shielded cable.



Optional extra
Foot control. Model SW-10 F With 10 metres of rubber cable.



Specifications

Capacity:	1000 Kg on top rolls
Capacity on rotation:	1000 Kg at face plate
Voltage:	220-240 VAC 1PH
Controller:	Digital VFD

External Dimensions

Length:	950 mm
Width:	650 mm
Height:	1050 mm
Net Weight:	192 Kg

© 2015

