



Proudly Australian Built



Technical Features

- * Boom reach, 2.0 m
- * Column reach, nozzle to floor 1.7m (standard) 2.0m with 300 mm base extension.
- * Variable speed range; column 0 – 200 mm/min while welding, boom in/out 0 – 500 mm/min .
- * Quality hand pendant with EM Shielded cable supplied as standard
- * All Welded, certified structural steel construction.
- * **Optional:** boom base, 1.9 x 1.3m with swivel base on 6 x groove wheels. 200 mm cross seam adjustment **SW-XYLA-30-30**. Laser Alignment System **SW-110LN/LF**. XY Joystick control.
- * Safety limits standard on X-Y axis
- * All welding/ EM shielded cables secured through boom
- * Fully enclosed IP65 electrical cabinet

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670
Fax: 61 8 9470 6680

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

Column & Boom Welder (Internal Drive) SW-CBWI-X20-Y17-STT



Welding equipment used:
Lincoln Powerwave **455M** &
dual head wire feed model **DH-10M**, suitable for up to 2.4mm SAW wire.

Specifications

- * Pipe Capacity: 2.0 m
- * Voltage: 220-240 VAC 1 ph
- * Speed control: Digital VFD
- * Overload Protection: Current (A) Voltage (V)
Torque (Nm)

External Dimensions

- Boom Length: 3.0 m
- Base: 1.3 x 1.9 m
- Column Height: 3.0 m (standard)
- Net Weight: 1200 Kg

© 2011

