



Proudly Australian Built



Product Information

SMITHWELD ENTERPRISES PTY LTD

Features

- * Boom reach, 2.0 m
- * Column height, nozzle to floor 2.5 m (standard) 3.0 m with height extension base optional.
- * Top lifting point for freight & positioning around the workshop
- * Variable speed range; Column 0 – 300 mm/min, Boom 0 – 500 mm/min
- * Quality hand pendant with EM shielded cable supplied as standard.
- * All welded, certified structural steel Construction
- * **Optional:** boom base 1.9 x 1.3m with 180° swivel 6 V wheels, includes lifting lugs. 200mm cross seam adjustment **SW-XYLA-30-30**. Laser Alignment System **SW-110LN/LF**
- * Safety limits on X & Y axis standard.
- * All Welding/ EM shielded cables secured through boom
- * Fully enclosed IP65 electrical cabinet.

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670
Fax: 61 8 9470 6680

Email: sales@smithweld.com

Column & Boom Welder (Internal Drive) **SW-CBWI-X20-Y25-SAW**



Specifications

- * Capacity: 1.7 - 2 m
- * Voltage: 220-240 VAC 1 ph
- * Speed control: Digital VFD
- * Overload Protection: Current (A) Voltage (V) Torque (Nm)

External Dimensions

- Boom Length: 3.0 m
- Base: 1.3 x 1.9 m
- Column Height: 3.0 M (standard)
- Net Weight: 1200 Kg

© 2009

